





ICC
EVALUATION
SERVICE®

ICC-ES EVALUATION REPORT #5045 with CBC-CRC Supplement (coming 2023)

SCREW FLANGE ATTACHMENT




CLIP ATTACHMENT





Screw Flange panels in this profile require additional material (drop/waste) and must be slit to a custom size. Inquire for custom pricing and availability.

PANEL ATTACHMENT CLIP

STANDOFF CLIP




STANDARD CLIP



KEY FEATURES

- 16" panel coverage
- 24 and 22 Tru-Gauge™ and .032" and .040 Aluminum. Screw Flange and Clip attachment available
- Custom 20 & 18 Tru-Gauge™ and .050" and .063" Aluminum. These require the use of high performance clip. (please inquire)
- 2' to 20'10" panel lengths
- Custom profiles available
- Vertical or Horizontal Wall Application
- Acceptable for use as a soffit panel
- Interchangeable panel widths and configurations
- Perforated options available (please inquire)

TESTING

-  ICC-ESR #5045 with CBC-CRC Supplement (coming 2023)
- ASTM E331 - Water infiltration (wall)
- ASTM E283 - Air infiltration (wall)
- ASTM E1592 - Negative structural uniform static air pressure
- ASTM E1680 - Air infiltration (roof)
- ASTM E1646 - Water infiltration (roof)
- ASTM A653/A924 - G90 Galvanized
- ASTM A792 - Zincalume/Galvalume AZ-50/55
- ASTM B209 - Aluminum Substrate

WEIGHT CHART

CI-7-16	TYPE	24 GA STEEL	22 GA STEEL	.032 ALUM	.040 ALUM
THICKNESS		0.0236"	0.0285"	0.032"	0.040"
WEIGHT/LINFT	CLIP ATTACH	1.691 LBS	1.982 LBS	0.801 LBS	0.972 LBS
WEIGHT/LSQFT	CLIP ATTACH	1.269 LBS	1.487 LBS	0.601 LBS	0.729 LBS
WEIGHT/LINFT	SCREW FLANGE	1.830 LBS	2.271 LBS	0.867 LBS	1.114 LBS
WEIGHT/LSQFT	SCREW FLANGE	1.373 LBS	1.703 LBS	0.651 LBS	0.835 LBS

ASTM E 1680/E283 Air Penetration	ASTM E 1646/E331 Water Penetration
12 PSF < 0.01 CFM/ft² - PASS	20.5 PSF - Pass
Intertek Test Result L5461.01-901-44 R1	Intertek Test Result L5460.01-901-44 R1
STRUCTURAL TESTING ASTM E1592 AND E330	
Intertek Test Result Q2599.09-301-44 R0	

NEGATIVE LOAD CHART WITH CLIP ATTACHMENT

				SECTION PROPERTIES						ALLOWABLE UNIFORM LOADS, psf For various clip spacings (i.e. span values)								
Width, in.	Gauge	Yield ksi	Weight psf	Top in Compression			Bottom in Compression			Negative Load								
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	1'	1.5'	2'	2.5'	3'	3.5'	4'	4.5'	5'
16	24	50	1.69	0.0338	0.0316	0.0504	0.0263	0.0284	0.0582	135.0	123.8	112.5	101.3	90.0	78.8	67.5	56.3	45.0
16	22	50	2.01	0.0421	0.0395	0.0639	0.0331	0.0357	0.0712	160.0	145.6	131.3	116.9	102.5	88.1	73.8	59.4	45.0
16	20	33	2.44	0.0593	0.0553	0.0921	0.0458	0.0497	0.0901	160.0	145.6	131.3	116.9	102.5	88.1	73.8	59.4	45.0
16	18	33	3.17	0.0804	0.0752	0.1267	0.0624	0.0676	0.1176	160.0	145.6	131.3	116.9	102.5	88.1	73.8	59.4	45.0


- Theoretical section properties for still panels have been calculated per AISI S100 Specifications for Design of Cold-Formed Steel Structural Members. Intertek Q2599.09-301-44 R0
- Charted Load/Span values are based on ASTM E1592-05, divided by a 2.00 Factor-of-Safety.
- Minimum recommended substrate (structure) recommendations:
 - Open-Framing (i.e. purlins)-16ga (design thickness 0.0566")
 - Plywood/OSB-15/32" or thicker is recommended to assure an effective degree of fastener thread engagement.
 - METAL DECK - 22ga (design thickness 0.0283")

POSITIVE LOAD CHART WITH CLIP ATTACHMENT

				SECTION PROPERTIES						ALLOWABLE UNIFORM LOADS, psf For various clip spacings (i.e. span values)									
Width, in.	Gauge	Yield ksi	Weight psf	Top in Compression			Bottom in Compression			Positive Load									
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	1'	2'	3'	4'	5'	6'	7'	8'	9'	10'
16	24	50	1.69	0.0338	0.0316	0.0504	0.0263	0.0284	0.0582	383.6	191.8	127.9	78.8	50.4	35.0	25.7	19.7	15.6	12.6
16	22	50	2.01	0.0421	0.0395	0.0639	0.0331	0.0357	0.0712	545.5	272.73	177.5	99.8	63.9	44.4	32.6	25.0	19.7	16.0
16	20	33	2.44	0.0593	0.0553	0.0921	0.0458	0.0497	0.0901	547.3	273.64	165.18	92.9	59.5	41.3	30.34	23.3	18.4	14.9
16	18	33	3.17	0.0804	0.0752	0.1267	0.0624	0.0676	0.1176	943.6	471.8	215.6	121.27	77.62	53.9	39.6	30.32	24.0	19.4

- Theoretical section properties for Steel panel have been calculated per 2020 AISI S100 North America Specifications for the Design of Cold-Formed Steel Structural Member.
- Allowable loads for Steel panels are calculated in accordance with 2020 AISI S100 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
- When panels are installed over solid or closely fitted sheathing, the capacity is limited to the capacity of the underlying sheathing.

PANEL ATTACHMENT



Fastener Notes:

- When possible, lap panels away from prevailing wind direction.
- 15/32" OSB: #10 Burr Buster fasteners.
- 15/32" Plywood: #10 GP Fastener. Screws should be long enough to penetrate through the bottom of the plywood by 3/8".
- Dimensional lumber: #10 GP. Screws should penetrate the lumber 1".
- 16ga (or less) Steel furring: #10 or #12 Fastener with DP-1
- All trim screws used for roof or wall applications should have EPDM sealing washers.